



CAPABILITIES

User managed AES-256 encryption for point-to-point voice telephony with Iridium 9575
AES-256 encrypted position location information (PLI)
Saber Nexus Suite: platform for end user AES-256 programmable key management, secure firmware updating, and device management
3.5 mm jack increases options for headset/microphone
Flexible charging options: - USB-C Port - Iridium Extreme OEM Charger - Ability to charge a 9575 while attached to the E-Clip
Visual feedback for power, encryption, tracking, and call status
Audio processing, including audio gain control, echo/noise cancellation, and silence detection
Ability to load three (3) AES-256 encryption keys and zeroize

DESIGN

USB-C - Iridium Extreme and E-Clip recharging - Encryption key loading - Firmware updates
Weight: 90.72 grams
Dimension (l x w x h): 2.05 x .841 x 2.43 in
3.5 mm headphone jack TRRS
9575 DC barrel connector
Encryption: AES Key Length: 256-bit
Device attaches to bottom of phone using solid point locking tabs
Not ITAR restricted, ECCN 5A992.c, and on DISA approved product list

E-Clip

Datasheet



Fully integrated rugged design that is compatible with the Iridium 9575 PTT and lightweight
Multi-function press buttons for power, answering/ending calls, and zeroization
LED Lights Status - Power - Encryption - Tracking - Call
Designed and manufactured in the U.S.



blacksabergroup.com